



PRODUCT INFORMATION



Product Name:	MICROLAC MICROPOROUS SYSTEM
Reference Number:	27-line
Coating Type:	Microporous primer undercoat and gloss based on light-fast, lead-free pigments.
Typical Uses:	Microporous paint system giving exceptional durability. Microporosity allows moisture-vapour to pass through the paint film reducing the tendency for wet rot, etc., and failure due to blistering, cracking, etc.
Colours Available:	White (full range to special order only, subject to 75-litre minimum Order.)
Appearance of Dried Film:	Gloss (Finish Coat)
Theoretical Coverage:	Approximately 10m ² per litre depending on film thickness applied.
Drying Time at 20°C: (Will vary with temperature, air movement etc.)	Touch Dry: 4 Hours Firm Dry: 8 Hours Overcoat: Overnight
Packaging:	5 litre containers.
Shelf Life:	2 years in unopened containers, when stored under cover in good storage conditions.
Storage:	Under cover within temperature range of 5°C to 32°C.

Continued/

Ref: 27-line

- Surface Preparation:** All new woodwork should be clean and dry with moisture content of less than 20%. If the woodwork has been previously painted, all the old paint should be removed to leave clean substrate. If the old coatings are not removed the microporous nature of the system will be ineffective.
- Microlac Primer/Undercoat:** Apply evenly by brush. Allow to dry overnight.
- Microlac Finish:** Apply two coats by brush, allowing overnight drying between coats.
- Clean Up:** Dacrylate Thinner R1.
- Health and Safety:** Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.