



PRODUCT INFORMATION



Product Name:	NORDAC TIMBER PROTECTION
Reference Number:	52-line
Coating Type:	MICROPOROUS Alkyd Resin with transparent light-fast pigmentation
Typical Uses:	Protection of hardwood and softwood timber, based on flexible resin with light-fast pigments. For interior and exterior use (see note overleaf). Microporous properties of the dried film allow permeation of water-vapour prolonging the life of the coating.
Colours Available:	Range of colours ex-stock with sheen gloss.
Appearance of Dried Film:	Sheen
Spreading Rate:	8-12m ² per litre depending on porosity or timber.
Drying Time at 20°C: (Will vary with temperature, air movement etc.)	Touch Dry: 4 hours Firm Dry: 8 hours Overcoat: Overnight
Packaging:	2.5 litre, 1litre and 0.5 litre containers.
Shelf Life:	2 years in unopened containers, when stored under cover in good storage conditions.
Storage:	Under cover within temperature range of 5°C to 32°C.

Continued/

Surface Preparation:

Ensure surface is clean and dry. **Lightly** abrade new wood in the direction of the grain. Moisture content of the wood should be less than 20%

Previously painted surfaces should be stripped back to bare wood and lightly sanded.

Application:

New Timber

- a) Apply two/three coats of Nordac Sheen evenly by brush. (Three coats are recommended for maximum exterior durability especially in exposed elevations)
- b) Timber previously painted with Nordac should be lightly abraded and two coats of Nordac applied.

Notes:

- i) Softwoods may be treated with a proprietary wood preservative prior to application of Nordac.
- ii) **Exterior Durability** In common with all coloured exterior varnishes, the **darker** stains will give better protection against degradation caused by ultra-violet light.
- iii) Where a gloss finish is required, the Nordac should be overcoated with Nordac Clear Gloss.

For long term protection Nordac Clear Gloss **alone** is not recommended for **exterior** use

Clean Up:

Dacrylate Thinner R1

Health and Safety:

Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.