




PRODUCT INFORMATION



Product Name:	OIL BASED WOOD PRIMERS
Reference Number:	96-Line
Coating Type:	Oil-Modified Alkyd.
Typical Uses:	Primer for use on wood, M.D.F. board, etc., with good opacity. Excellent durability/flexibility.
Colours Available:	White - 96-1 Cream - 96-4 Pink - 96-8
Appearance Of Dried Film:	Low sheen.
Theoretical Coverage:	8 to 15 M ² per litre depending on texture, porosity of substrate, etc.
Drying Time At 20°C: (Will Vary With Temperature, Air Movement etc.).	Touch Dry: 4 Hours Firm Dry: 8 Hours Overcoat: Overnight
Packaging:	5 litre containers.
Shelf Life:	2 years or longer in unopened containers when stored under cover in good storage conditions.
Storage:	Under cover within temperature range of 5°C to 32°C.

Continued/

Surface Preparation: Ensure substrate is clean and dry. If timber is treated with preservative, i.e., Vac-Vac, Protim, etc., allow to dry before painting, ensuring good ventilation, for at least 48 hours.

Stack timber so that air-circulation assists drying of preservative.

Application: **By Brush, Roller or Spray**

Conventional spray or airless spray – add 10-15% of Dacrylate Thinner R70 to obtain optimum spray characteristics.

May also be applied using Timber Vacuum Coating Machines.

Clean-Up: Dacrylate Thinner R1 or R70.

Health and Safety: Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

Issued: January 2001

SW/DAE/CR/CS