



PRODUCT INFORMATION



Product Name:	CLEAR ACRYLIC GLAZE
Reference Number:	103-1
Coating Type:	Water-borne acrylic copolymer.
Typical Uses:	<ol style="list-style-type: none">1) Clear glaze for application over emulsion paints.2) Clear water-borne sealer for concrete to reduce 'dusting'.3) Clear water-borne sealer/glaze for timber, MDF etc.
Surface Preparation:	Ensure substrate is clean and dry.
Spreading Rate:	Approximately 10m ² per litre depending on substrate. (Coarse or porous surfaces will reduce spreading rate.)
Application:	Apply by brush or roller. Thin with up to 10% water for spray application. (When used as sealer for concrete or wood etc, thin with 10% water.)
Drying Time At 20°C: (Will Vary With Temperature, Air Movement etc.).	Touch Dry: 30 minutes. Firm Dry: 2 hours. Overcoat: 2 hours.
Shelf Life:	2 years or longer in unopened containers, when stored under cover in good storage conditions.
Storage:	Under cover within temperature range of 5°C to 32°C. <u>Protect from frost.</u>
Clean-Up	Clean water.
Health and Safety:	Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

Issued: August 2001

SW/DAE/CR/WHC