



# PRODUCT INFORMATION



<b>Product Name:</b>	<b>DAC SATIN AND DAC MATT</b>
<b>Reference Number:</b>	104-line and 100-line.
<b>Coating Type:</b>	Acrylic emulsion.
<b>Typical Uses:</b>	High quality water-based paint for interior and exterior use on masonry, cement, plaster, concrete, asbestos, hardboard, timber, etc. Ideal for anaglypta and woodchip papers. The satin finish gives a durable velvet sheen. Coatings are hardwearing and scrub-resistant.
<b>Colours Available:</b>	As current shade card. Full range to special order, may be subject to minimum order quantity.
<b>Appearance of Dried Film:</b>	Satin finish or matt finish.
<b>Application rate:</b>	10-15m <sup>2</sup> per litre depending on porosity and texture of surface.
<b>Drying Time At 20°C: (Will Vary With Temperature, Air Movement etc.).</b>	<b>Touch Dry:</b> 1 hour. <b>Firm Dry:</b> 2-4 hours. <b>Overcoat:</b> 2-4 hours.
	<b>Note:</b> Drying times of emulsion paints will vary widely depending upon humidity, air circulation, ventilation, etc.
<b>Packaging:</b>	1 litre, 2.5 litre and 5 litre containers
<b>Shelf Life:</b>	2 years or longer in unopened containers, when stored under cover in good storage conditions.
<b>Storage:</b>	Under cover within temperature range of 5°C to 32°C. <u>Protect from frost.</u>

**Continued/**

- Surface Preparation:** All surfaces must be clean, dry, and free from oil, grease, etc. Remove all loose, friable material, e.g. loose plaster, old flaking paint, etc.
- On new and/or porous surfaces, thin first coat with up to 30% of clean water. Underbound substrates should be sealed with Dacrylate Masonry Sealer ref: 150-50.
- Application:** **Do not apply at temperatures below 5°C.**
- May be applied by brush, roller, conventional or airless spray.
- Up to 15% of clean water may be added to achieve optimum spray characteristics.
- Clean-Up:** Water – clean equipment **IMMEDIATELY**, do not allow emulsion to dry.
- Health and Safety:** Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.