




PRODUCT INFORMATION



Product Name:	ACRYLIC WOOD PRIMER
Reference Number:	116-Line.
Coating Type:	Acrylic-vinyl copolymer.
Typical Uses:	High opacity, water-borne primer for wood, M.D.F., hardboard etc.
Colours Available:	White, Pink and Cream.
Surface Preparation:	Ensure substrate is clean and dry.
Application Rate:	10-12m ² per litre.
Application:	Brush, roller or spray.
Drying Time At 20°C: (Will Vary with Temperature, Air Movement etc.).	Touch Dry: 15-20 minutes. Firm Dry: 1 hour. Overcoat: 1 hour with water-borne coatings. - 4 hours with solvent-borne coatings.
Shelf Life:	2 years or longer in unopened containers when stored under cover in good storage conditions.
Storage:	Under cover within temperature range of 5°C to 32°C.
Clean-Up:	Clean all equipment <u>IMMEDIATELY</u> after use with clean water.
Health and Safety:	Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

Issued: August 2001

SW/DAE/CR