




PRODUCT INFORMATION



Product Name:	WATER-BASED DUAL PRIMER															
Reference Number:	150-Line															
Coating Type:	Water-based acrylic.															
Typical Uses:	Wood colouring and priming base coat for interior and exterior use. May be overcoated with conventional paint or wood stain. Microporous to control water-vapour diffusion. Pigmentation minimises degradation of timber by ultra-violet sunlight.															
Colours Available:	<table><tr><td>Brown</td><td>-</td><td>Ref:150-390</td></tr><tr><td>Light Oak</td><td>-</td><td>Ref:150-181</td></tr><tr><td>Medium Oak</td><td>-</td><td>Ref:150-206</td></tr><tr><td>Mais Wood Stain</td><td>-</td><td>Ref:150-248</td></tr><tr><td>Yellow Ochre</td><td>-</td><td>Ref:150-331</td></tr></table> <p>Other colours to special order (may be subject to minimum order requirement).</p>	Brown	-	Ref:150-390	Light Oak	-	Ref:150-181	Medium Oak	-	Ref:150-206	Mais Wood Stain	-	Ref:150-248	Yellow Ochre	-	Ref:150-331
Brown	-	Ref:150-390														
Light Oak	-	Ref:150-181														
Medium Oak	-	Ref:150-206														
Mais Wood Stain	-	Ref:150-248														
Yellow Ochre	-	Ref:150-331														
Appearance Of Dried Film:	Low sheen.															
Volume Solids:	Approximately 15m ² per litre depending upon porosity of timber, film build, etc.															
Drying Time At 20°C: (Will Vary With Temperature, Air Movement etc.).	Touch Dry: 20 minutes. Firm Dry: 2 hours. Overcoat: 2 hours with water-based systems. Overnight with solvent-based systems.															
	Note: Drying times of water-based paints will widely depend upon humidity, air circulation, ventilation, etc.															
Packaging:	5 litre and 20 litre containers.															
Shelf Life:	2 years or longer in unopened containers when stored under cover in good storage conditions.															
Storage:	Under cover within temperature range of 5°C to 32°C.															

Continued/

- Surface Preparation:** All timber should be adequately preserved, clean, dry and free of contaminants.
- Application:** Apply by brush, spray or automatic timber coater.
- Clean-Up:** Clean equipment **immediately** after use with water. Do not allow primer to dry.
- Health And Safety:** Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.