



PRODUCT INFORMATION



Product Name:	MARCLEAN GP
Reference Number:	150-198 British Rail Catalogue Number 7/57457/8.
Coating Type:	General purpose graffiti removal solution – a blend of suitable solvents together with additives supplied as a gel.
Typical Uses:	For the removal of sprayed graffiti, felt marker pen, etc., from sealed surfaces, and from many plastics and aged alkyd paints.
Packaging:	0.5 litre, 1 litre, 2.5 litre and 5 litre lever-lid containers (also available in aerosols).
Shelf Life:	12 months in unopened containers.
Storage:	Under cover within temperature range of 5°C to 32°C.
Application:	<p>Marclean GP should be applied to the graffiti-contaminated surface by brush and allowed to stand for a few minutes. It should then be agitated to break up the graffiti and the excess wiped off (it may be wiped back into a suitable container from a smooth surface with a suitable implement). If necessary, repeat the process where the graffiti is still present.</p> <p>On complete removal of the graffiti, thoroughly wash the area with water with a small amount of detergent added.</p> <p>Prior to using Marclean GP, a small trial area should always be carried out before large scale graffiti removal is undertaken. The trial area should be washed with water as soon as the graffiti has been removed and the substrate examined to ascertain whether any damage to the substrate has taken place.</p> <p>If the graffiti which has been applied is made up of alkyd coatings, Marclean GP will only remove such graffiti very slowly. Quicker removal will be achieved using a proprietary solvent-based paint remover observing the usual precautions for such a product.</p>

Continued/

Ref:150-198

Application Continued:

Marclean GP may also be used to remove graffiti from unsealed surfaces such as brick, stone or concrete. However, there may be an “image” of the graffiti damage remaining due to the amount of rubbing and brushing required to remove the stain.

The most effective means of removal on unsealed surfaces is by wet abrasive blasting and ideally this should be adapted as a cleaning process prior to sealing with Margard SP Clear Finish.

Once sealed these surfaces can be effectively cleaned with Marclean GP Graffiti Removal Solution.

Health And Safety:

Please see relevant MSDS sheet.

Data sheets are issued to supply **general information** on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

Issued: April 1999

SW/DAE/CS